



### APPLICATION:

Panel Assembly for thermocouple and RTD circuits for mounting in control rooms, test stands, laboratory applications, pilot plants, etc.

### CONSTRUCTION:

This panel consists of the panel set BM-20.059-x fitted with the Standard panel inserts PSI-... For further details see separate specification sheets

### WIRE SIZE:

- Accepts wires from 0,2 mm to 2,0 mm

### TEMPERATURE RATING:

200 °C Max.

### ORDERING CODE:

PAS-xx

For last two digits 'xx' see the table below

Calibration Code			E	J	K	N	T	U	R/S	C	B
Compensation material for									Pt13Rh Pt	W5Re W26Re	Pt6Rh/ Pt30Rh
Material Positive			NiCr	Fe	NiCr	NiCrSi	Cu	Cu	Cu	CPX	Cu
Material Negative			CuNi	CuNi	NiAl	NiSi	CuNi	Cu	Alloy 11	CNX	Cu
IEC Color Code			Violet	Black	Green	Pink	Brown	White	Orange	Red	Grey
Circuits	Rows	Color Body Dimensions L x H									
1	1	38 x 38	1-EI	1-JI	1-KI	1-NI	1-TI	1-UI	1-RI	1-C	1-BI
6	1	146 x 67	6-EI	6-JI	6-KI	6-NI	6-tI	6-UI	6-RI	6-C	6-BI
8	1	184 x 67	8-EI	8-JI	8-KI	8-NI	8-TI	8-UI	8-RI	8-C	8-BI
12	1	260 x 67	12-EI	12-JI	12-KI	12-NI	12-TI	12-UI	12-RI	12-C	12-BI
24	2	260 x 115	24-EI	24-JI	24-KI	24-NI	24-TI	24-UI	24-RI	24-C	24-BI