

Detaylı Bilgi İçin Ürün Resmine Tıklayınız



MDM25, farklı sonda konfigürasyonları bulunan, taşınabilir, pille çalışan bir portatif nem ölçer cihazıdır. E

Ürün Özellikleri

- Ekranlar % RH ve Sıcaklık, artı çiy noktası, mutlak nem ve ıslak termometre sıcaklığı
- Kullanımı kolay
- Uzun vadeli istikrar: 12 ay içinde ± 1 RH

Portatif

Performans

Measurements: %RH, °C/°F Ta, °C/°F Td, g/m³, °C/°F Tw

Mekanik Özellikler

Ingress Protection
IP54 - Hand meter only
Hand Meter Housing Material Molded polymer housing ABS + rubber surround
Weight
300g (10.58oz)
Display Resolution
Graphic LCD 128 x 64 pixels

Elektriksel Giriş/Çıkış

Supply Voltage 4.5 V (3 x AA batteries - provide approximately 70 hours of operation)
Electrical Connections M9 5-way triad connector

Sondalar

Performans

Measurement Range (RH) 0-100% RH
Accuracy at 25°C (77°F) $\pm 1\%$ RH
Stability $\pm 1\%$ RH / year
Response time - RH Sensor 10 sec typical (for 90% of the step change)
Measurement & Operating range (T) -10 to 50°C (-14 to 122°F)
Fixed and Standard Probe

Sword Probe

Remote Probe

-20 to +80°C

-20 to +100°C

-20 to +150°C

Accuracy at 25°C Humidity

Fixed Probe

Remote Probes ±2% RH (10 - 90% RH)

±2% RH (5 - 95% RH)

Mekanik Özellikler

Weight

Fixed Probe (FPR) 30g

Standard Probe (SPR) 90g

Sword Probe (SWPR) 500g

Round 300mm Probe (HTPR300) 380g

Round 500mm Probe (HTPR500) 620g