

[Ana Sayfa](#) > [rnler](#) > [Tork Kuvvet rn Kategorisi](#)

Detaylı Bilgi İin rn Resmine veya Bařlıđına Tıklayınız

Model
Aıklama

lm Aralıđı [N·m]

Sertifikalar



AB

50..500 kg



For Platforms up to 800x800 mm
To 3000d OIML R60, 5000d NTEP



AG

2.5 kg or 5..100 kg



For Platforms up to 200x200 mm (2.5 kg),
400x400 mm (5..100 kg)
Highest Precision (to 6000d) OIML R60,
5000d NTEP



AH

30..200 kg



For Platforms up to 500x500 mm
To 6000d OIML R60



AHN

250 kg



For Platforms up to 500x500 mm

To 6000d OIML R60



AK

6..300 kg



Stainless Steel, Level of Protection IP68
For Platforms up to 600x600 mm
To 3000d OIML R60, 5000d NTEP



AL

3..30 kg



For Platforms up to 300x350 mm,
(200x240 mm for AL3 kg)
To 3000d OIML R60



AP

75..635 kg



For Platforms up to 700x700 mm
To 3000d OIML R60
Flat Designed (47 mm)



AP1500

1500 kg



For Platforms up to 1000x1000 mm
To 3000d OIML R60
Flat Designed (68 mm)




AQ

5..35 kg



For Platforms up to 350x350 mm

To 3000d OIML R60, 5000d NTEP
Flat Designed (22 mm)



AR 0.2..1.2 kg
For Platforms up to 150x150 mm
Low Cost Load Cell
Flat Designed (22 mm)



AXH 100..500 kg



Stainless Steel, Level of Protection IP69K
For Platforms up to 600x600 mm
To 3000d OIML R60



AXL 10..75 kg



Stainless Steel, Level of Protection IP69K
For Platforms up to 400x400 mm
To 3000d OIML R60



BE 1..10 kg
For Platforms up to 150x150 mm
Low Cost Load Cell
Flat Designed (26 mm/12 mm)



PM 150 kg
For Platforms up to 600x600 mm
Level of Protection IP67
Frontally Mounted